

www.acramachinery.com

ACRA 1440JN PRECISION ENGINE LATHE



FEATURES:

- Hardened And Ground Bed Way
- Tang In Tailstock
- Safety Electrical Disconnect
- Foot Brake
- Low Voltage Controls
- Adjustable Apron Clutch
- Inch/Metric Gear Box
- Full Length Splash Guard
- Pressure Lubrication For Headstock
- 5 Position Feed Kick Out
- External Oil Filter
- 3 Bearing Supported Spindle

STANDARD ACCESSORIES:

- 8" 3 Jaw Chuck
- 10" 4 Jaw Chuck
- Steady/Follow Rest
- Splash Guard
- Coolant System
- Tool Box With Tools
- Face Plate
- Halogen Light
- Micro Bed Stop
- Gap Bed

OPTIONAL ACCESSORIES:

- Taper Attachment
- Taper Attachment Installation
- Lever Type 5C Collet Closer JFK
- Import Collet Closer
- Sargon Digital Read-Out
- Sony Digital Read-Out
- Anilam Digital Read-Out
- Newall Digital Read-Out
- D.R.O. Installation
- Import Quick Change Tool Holder

ACRA 1400JN PRECISION ENGINE LATHE

SPECIFICATIONS		1440 JN
CAPACITY	Swing Over Bed	14"
	Swing Over Cross Side	8.3"
	Swing In Gap	19.7"
	Distance Between Centers	40"
	Bed Width	11.8"
SPINDLE	Spindle Nose	D1-6
	Spindle Bore	2"
	Taper of Spindle	MT NO.5
	Spindle Speeds	12 SPEEDS 76~2000 RPM
TRAVEL	Cross Slide	10.4"
	Compound Slide	4"
THREADS & FEEDS	Inch Threads	23KINDS 4~48TPI
	Metric Threads	17KINDS 0.5~6.5MM
	Longitudinal Feed	0.0015~0.0196 IPR
	Cross Feed	0.00075~0.0098 IPR
TAIL STOCK	Quill Diameter	2.4"
	Quill Travel	4.7"
	Quill Taper	MT NO.4
POWER	Spindle Drive Motor	5 HP
	Voltage	220/440V AC / 3PH
	Coolant Pump	1/8 HP 220/440V AC / 3 PH
WEIGHT	Net Weight	3,750 LBS
	Dimension L.xW.xH.	85.8" x 33.5" x 46.7"

NOTE: The manufacturer reserves the right to modify the design, specifications, & mechanisms to improve the performances of the machines without notice. All specifications above are for your reference only.