

ACRA 1600 GNX FEL MAGNUM-CUT CENTER LATHE



STANDARD ACCESSORIES:

- 10" 3 Jaw Chuck
- 12" 4 Jaw Chuck
- Splash Guard
- Face Plate
- Coolant System
- Tool Box With Tools
- Steady/Follow Rest
- Gap Bed

OPTIONAL ACCESSORIES:

- Micro Bed Stop
- Follow Rest
- Taper Attachment
- Taper Attachment Installation
- Lever Type 5C Collet Closer JFK
- Import Collet Closer
- Sargon D.R.O. 40"
- Sargon D.R.O. 60"
- Sony D.R.O. 40"
- Sony D.R.O. 60"
- Anilam D.R.O. 40"
- Anilam D.R.O. 60"
- Newall D.R.O. 40"
- Newall D.R.O. 60"
- D.R.O. Installation
- Import Quick Change Tool Holder
- Halogen Light
- Live Center "MT 4"

ACRA 1600 GNX FEL MAGNUM-CUT CENTER LATHE

SPECIFICATIONS		1640 / 1660 GNX
CAPACITY	Swing Over Bed	16"
	Swing Over Cross Side	10"
	Swing In Gap	26"
	Distance Between Centers	40" / 60"
	Bed Width	13.20"
SPINDLE	Spindle Nose	D1-8
	Spindle Bore	3 1/8"
	Taper of Spindle	MT NO.5
	Spindle Speeds	12 STEPS 42~1800 RPM
TRAVEL	Cross Slide	8"
	Compound Slide	4"
THREADS & FEEDS	Inch Threads	65 KINDS 1 5/8~72 TPI
	Metric Threads	28 KINDS 0.5~20 MM
	Module Threads	24 KINDS 0.25~10
	Diametrical Threads	45 KINDS 3.25~96
	Longitudinal Feed	0.0015~0.0913 IPR
	Cross Feed	0.0006~0.0365 IPR
TAIL STOCK	Quill Diameter	3"
	Quill Travel	5"
	Quill Taper	MT NO.4
POWER	Spindle Drive Motor	7.5 HP
	Coolant Motor	0.12 HP
	Voltage	N/A
WEIGHT	Net Weight	4,187 LBS / 4,850 LBS
	Dimension L.xW.xH.	91.3" x 37.8" x 53.5" / 111" x 37.8" x 53.5"

NOTE! The manufacturer reserves the right to modify the design, specifications, & mechanisms to improve the performances of the machines without notice. All specifications above are for your reference only.