www.acramachinery.com ACRA 2600/3100/4400 CW PRECISION ENGINE LATHE



STANDARD ACCESSORIES:

- 3 Jaw Chuck
- 4 jaw Chuck
- Coolant System
- Rapid Travel

- Steady/Follow Rest
- 4 Way Tool Holder
- Face Plate
- Halogen Light

OPTIONAL ACCESSORIES:

Taper Attachment

Installation of Taper Attachment

SPECIFICATIONS	2630/2660/26120/26160/26200 CW	3160/31120/31160/31200 CW	4460/44120/44160/44200 CW
Swing Over Bed	24.8"	31.5°	43.7"
Swing Over Cross Side	13.78"	18.9"	31.5"
Swing In Gap	31.5"	39.37"	39.37"
Spindle Bore	5.12"	5.12"	5.12"
Spindle Nose	D1-11	D1-11	D1-11
Spindle RPM	7-1000	5-720	5-640
Main Motor	20 HP	20 HP	20 HP
Voltage	220V/440V AC / 3PH	220V/440V AC / 3PH	220V/440V AC / 3PH
Weight	7,495/8,157/10,362/12,787/14,991 LBS	10,803/12,125/13,448/15,212 LBS	12,125/13,448/14,771/16,535LBS

Note: The manufacturer reserves the right to modify the design, specifications, & mechanisms to improve the performances of the machines without notice. All specifications above are for your reference only.