www.acramachinery.com ACRA 920CQ BENCH LATHE



FEATURES:

- Reinforced Cross Ribs
- Cast Iron Quick-Change Gear Box
- Headstock With Tapered Roller Bearings
- Hardened And Ground Ways

OPTIONAL ACCESSORIES:

Stand

STANDARD EQUIPMENT:

- 4" 3 Jaw Chuck
- Face Plate
- Steady/Follow Rest

- Metric Change Gears
- 7 1/2" 4 Jaw Chuck
- 4 Way Tool Holder

| | SPECIFICATIONS | 920 CQ |
|-----------------|--------------------------|---------------------|
| CAPACITY | Swing Over Bed | 9" |
| | Swing Over Cross Side | 5 1/4" |
| | Distance Between Centers | 20" |
| SPINDLE | Spindle Nose | 1 1/2" x 8 TPI |
| | Spindle Bore | 3/4" |
| | Taper of Spindle | MT No 3 |
| | Spindle Speeds | 130~2000 RPM |
| TRAVEL | Tailstock Spindle Travel | 1.57" |
| | Cross Slide Travel | 4 1/2" |
| | Compound Travel | 2" |
| THREADS & FEEDS | Inch Threads | 27 KINDS 8~56 TPI |
| | Metric Threads | 11 KINDS 0.5mm~3mm |
| | Longitudinal Feed | (2) 0.005", 0.007" |
| TAIL STOCK | Quill Taper | MT NO.2 |
| POWER | Spindle Drive Motor | 3/4 HP |
| | Voltage | 100/220V AC / 1PH |
| WEIGHT | Net Weight | 190 LBS |
| | Shipping Weight | 250 LBS |
| | Dimension | 38" x 18 1/2" x 16" |

Note: The manufacturer reserves the right to modify the design, specifications, & mechanisms to improve the performances of the machines without notice. All specifications above are for your reference only