

www.acramachinery.com
ACRA BS 250 HORIZONTAL BANDSAWS



FEATURES:

- Horizontal Bandsaws
- Large Handwheel And Build-In Gauge For Easy Blade Tensioning
- Built In Coolant, And Coolant Is Distributed Through The Blade Guides
- Carbide Tungsten Blade Guide Supported By Bridge Type Portable Frame
- Blade Brush Is Build-In And Self Propelled
- Quick Positioning Clamping Vise With Fully Adjustable Jaws The Rapid Action Vice

- With 90 To 60 Full Mitering
- Removable Cip Tray For Easy Clean Up
- Fully Adjustable Hydraulic Down Feed With Separate On/Off Valve
- Heavy Duty Cast-iron Construction
- Low Voltage Control With Overload Protection
- Centralized Control Panel
- Standard Coolant

SPECIFICATIONS		BS 250A	BS 250AS	BS 250V	BS 250VS
Capacity (Round)	90°	10"	10"	10"	10"
	45°	8 1/2"	8 1/2"	8 1/2"	8 1/2"
Capacity (Rect.)	90°	10" x 15"	10" x 15"	10" x 15"	10" x 15"
	45°	10" x 9 1/2"	10" x 9 1/2"	10" x 9 1/2"	10" x 9 1/2"
Throat Depth		10 1/2"	10 1/2"	10 1/2"	10 1/2"
Swivel Base		0	60~90°	0	60~90°
Blade Speed		82,131,167,233 FPM	82,131,167,23 FPM	82~259 FPM	82~259 FPM
Blade Size		1" x 0.35" x 135"	1" x 0.35" x 135"	1" x 0.35" x 135"	1" x 0.35" x 135"
Main Motor		2 HP	2 HP	2 HP	2 HP
Voltage		220/440V AC/3PH	220/440V AC/3PH	220/440V AC/3PH	220/440V AC/3PH
Bed Height		23 1/2"	23 1/2"	23 1/2"	23 1/2"
Floor Space		68" x 30" x 44 1/2"	68" x 30" x 44 1/2"	68" x 30" x 44 1/2"	68" x 30" x 44 1/2"
Weight		920 LBS	1,100 LBS	920 LBS	1,100 LBS

NOTE! The manufacturer reserves the right to modify the design, specifications, & mechanisms to improve the performances of the machines without notice. All specifications above are for your reference only.